



Screwdriving technology

Automation

Speed Regulator

Innovative solution to equalize air-motor speed fluctuations

A speed regulator is suitable for all applications where a constant speed at changing loads is needed.

- universal usability because of free parameter-setting •
- large speed-range up to 80,000 rpm •
- high-resolution and accurate control •







DEPRAG Speed Regulators

Universal usability because of free parameter-setting

The Speed regulator can be adjusted to fit different applications. With some applications, the speed adjustability is the main focus. Other applications however, require a high rate of speed accuracy. The DEPRAG speed regulators allow a free parameter-setting that can accommodate both cases and they are therefore universally usable.

Application Example:

Agitator, ADVANCED LINE Air-Motor Model No. 67-028R Required regulator characteristics: a definite need for a constant speed and a short reaction time when load changes.

Solution. Speed Regulator with a consistency of ± 5 rotations/min, reaction time of maximum 2 seconds when load changes.

Large Speed-Range – up to 80,000 rpm

The full range of the DEPRAG air motors is covered with this speed regulator. So, even a motor with a very low speed can be regulated. The speed can be measured and controlled, starting at a whole revolution down to a 1/32nd of a revolution.

High-Resolution and Accurate Control

An air-motor with a low speed range can be regulated with utmost processing reliability. The speed ranging from a full-revolution to a 1/32nd of a revolution can be acquired and adjusted to the nominal speed. Even air-motors with high speeds can be acurately actuated and controlled by the proportional-valve. The output signal for the control of the valve amounts to 0 - 10 V; the resolution of the control voltage is therefore 2.5 mV.

Design and Function

The DEPRAG speed regulator consists of a non-contacting speed sensor that is directly integrated into the air-motor between the actual vane-motor and the gearing.



The sensor acquires the actual speed and relays a digital signal to the regulator. The regulator "knows" the required nominal value, which can easily be input into the LC-display of the control.

The control module is ready for the simple DIN-rail installation into the customer's control box. The required speed can easily be input into the operator-friendly LCdisplay.

A proportional-valve that regulates the airflow of the air-motor is actuated, when deviations occur.

Do you want to learn more about the speed regulators and are you looking for a solution? Our technical advisors are ready to help!





P.O. Box 1352, D-92203 Amberg, Germany Carl-Schulz-Platz 1, D-92224 Amberg Phone (+49) 9621 371-0, Fax (+49) 9621 371-120 www.deprag.com info@deprag.de

